

→ 4005 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times | wide, 16" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut model (4014-2 SMC in US / 4005 SMC in Canada) meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on super micro-cut cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy chain drive and dust-proof gearbox housing | high quality wooden cabinet mounted on casters | convenient shred bin | 40 gallon shred volume

Dimensions (D x W x H): 23 % x 25 % x 39 % inches, Shipping weight: 343 lbs. (strip-cut) / 378 lbs. (cross-cut) / 390 lbs. (super micro-cut).







CAPACITY INDICATOR

"ECC" (Electronic Capacity Control) indicator monitors capacity levels during operation.

→ 4005 STRIP-CUT

Strip width	1/4"
Sheet capacity	50-52*
Security level	2
Feed opening	16''
Max. horsepower	2 1/8

→ 4005 CROSS-CUT

Particle size	3/16" x 1 ½"
Sheet capacity	30-32*
Security level	3
Feed opening	16''

Max. horsepower $2 \frac{1}{8}$ \rightarrow 4005 CROSS-CUT

Particle size	3/32" x 5/8"
Sheet capacity	18-20*
Security level	4
Feed opening	16"
Max. horsepower	2 1/8

→ 4014-2 SMC / 4005 SMC

Particle size	1/32" x 3/16"
Sheet capacity	12-16*
Security level	6
Feed opening	16"
Max horsenower	2 1/6

 may vary due to variations in paper and power supply

nate and subject to change. © MBM Corporation, 3/2011.



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com

20 amp. dedicated line required



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com Dealer:

